

INSTALLATION INSTRUCTIONS

1. Top Platform & Rack Legs

Assemble the rack legs to the **inside of the top platform** using **4 pcs M5 × 15 flat head Allen screws** and **lock nuts**.

- The leg with **less top flare** faces forward
 - **Strap holders** face inward
-

2. Cage Foot Installation (Optional)

When using cage feet, assemble the **cage foot outside the rack leg**, with the **stainless bracket inside the rack leg**, using **4 pcs spring washers** and **M5 × 18 flat head Allen screws**.

If cage feet are **not used**, replace them with **2 pcs M5 lock nuts**.

3. Fork Mount Installation

Install **Cage Wednesday** onto the fork mounts using **M5 × 18 screws**, with **long spacers and washers** as required.

4. Strut Installation

Use the **strut bolts**, **M12 aluminum washers (4 mm thickness)**, and **M6 hex lock nuts** to attach the two struts to the rack.

- Normally, install struts **inside the rack legs**
- For **mountain bike forks**, install struts **outside the rack legs**

REQUIREMENTS

1. Fork & Frame Mounting

- **M5 eyelets** at the fork end
- **M5 mounts** on the **outer side of the fork legs**

2. Rack Mount Spacing

- Standard rack mount spacing: **130 mm**

If spacing is insufficient, you may:

- Assemble rack legs **outside the top platform**, or

- Install brackets **outside the rack legs**

→ Longer M5 bolts and spacers may be required

3. Rack Size & Wheel Compatibility

Rack Size M

- Rack height: **365 mm**
- Recommended for **26"–28" wheels**

Rack Size L

- Rack height: **390 mm**
- Recommended for **29" wheels and above**